

HG "mould spray"

DESTROYS MOULD, ALGAE, FUNGUS AND MOSS
REMOVES BLACK SPOTS.

- APPLICATION

On silicone and rubber seals, plaster and tile grouts in areas of high humidity both inside and outside.

- DIRECTIONS FOR USE

Apply HG "mould spray" directly to mould and algae but scrape away layers of fungus and moss before use. Fix the spray attachment onto the bottle. Spray the surface from a distance of approximately 5 cm (2 inches). Leave the product to work for 10 minutes. Flexible silicon seals and surfaces that are badly stained should be sprayed again after 10 minutes. When clean, rinse the treated area with plenty of water and a sponge.

- PRODUCT INFORMATION

Characteristics	: bleaching liquid
Density	: ± 1.09 g/ml
pH	: 13 – 13.5
Usage	: 4 - 6 m ² /L
Active matter	: 4.5 %
Components	: sodium hydroxide, sodium hypo chlorite, Mixture of lauryl ether carboxylic acid and sodium octyl sulphate and water

- PACKAGING : 6 x 0.5 L

- PRECAUTIONS

Store upright in a cool dark place. Storage life: see base of bottle. Avoid splashes on clothes. **R36/38**-Irritating to eyes and skin. **S2**-Keep out of reach of children.

S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. **S37**- Wear suitable gloves. **S46**- If swallowed, seek medical advice immediately and show this container or label. **S50**- Do not mixing with acids.

S64-If swallowed, rinse mouth with water (only if the person is conscious). Caution! Do not use in combination with other products, hazardous gasses (chlorine) could be released.